

NorAM M & M3 Class Paint Booths

Specifications and features are subject to change.

M Class Paint Booths

Dimensions

- 14' wide x 25' long x 9' high (inside)
- 14'5" wide x 25'5" long x 11' high (outside)
- Optional length extensions in 2'6" sections

Construction

- Manufactured to NFPA-33, 2000 standards
- 18 gauge galvanized steel
- Bolt together assembly on 6" centers
- Strong post and beam design
- Large 6" x 6" x 1/4" door hinges, zinc plated, adjustable
- Tri-fold drive door measures 9' x 10'
- Personnel doors feature large observation window
- Panic push exit door hardware
- Lever action double-rod stationary door closers
- 24" stainless steel door pull handles
- "D" style rubber door gasketing for an airtight seal

Lighting

- (10) ceiling mounted custom 4-tube fixtures
- Asymmetrical reflectors for shadow-free illumination
- Color correcting 97 CRI/6000°K high intensity 48" bulbs

Pit/Extraction System and Filtration

Downdraft Models

- Full downdraft airflow
- 30" x 15' single row pit kit standard
- Ceiling plenum measures 10' x 25' x 18"
- Hinged access ceiling filtration

Semi-Downdraft Models

- Rear wall extraction, 2'6" x 10'
- 18 gram fiberglass filter media
- Hinged access ceiling filtration

Side-Draft Models

- (2) 2'6" x 10' side exhaust boxes
- 18 gram fiberglass filter media
- 30" exhaust fans

Options/Upgrades

- ETL listed digital control panels
- ETL listed Mach-3 and Mach-3X heat systems
- ETL listed "Opti-Quiet" exhaust fans
- Full drive through configuration
- Pit kit upgrades (downdraft only)
- Above ground metal basement (downdraft only)
- Attached paint mixing and storage rooms
- Matching prep/refinishing stations
- VFD cabin pressure adjustment
- Remotely mounted control panel(s)
- "Opti-Cure" PLC/VFD control panel
- "Opti-Light" 360° lighting package upgrade, 6-tube fixtures
- Wall lighting kits
- Duct packages

M3 Class Paint Booths

Dimensions

- 14' wide x 25' long x 9' high (inside)
- 14'5" wide x 25'5" long x 11' high (outside)
- Optional length extensions in 2'6" sections

Construction

- Manufactured to NFPA-33, 2000 standards
- 18 gauge galvanized steel, white finish
- Bolt together assembly on 6" centers
- Strong post and beam design
- Large 6" x 6" x 1/4" door hinges, zinc plated, adjustable
- Tri-fold drive door measures 9' x 10'
- Personnel doors feature large observation window
- Panic push exit door hardware
- Lever action double-rod stationary door closers
- 24" stainless steel door pull handles
- "D" style rubber door gasketing for an airtight seal

Lighting

- (10) ceiling mounted custom 6-tube fixtures
- Asymmetrical reflectors for shadow-free illumination
- Color correcting 97 CRI/6000°K high intensity 48" bulbs

Pit/Extraction System and Filtration

Downdraft Models

- Full downdraft airflow
- 30" x 15' single row pit kit standard
- Ceiling plenum measures 10' x 25' x 18"
- Hinged access ceiling filtration

Semi-Downdraft Models

- Rear wall extraction, 2'6" x 10'
- 18 gram fiberglass filter media
- Hinged access ceiling filtration

Side-Draft Models

- (2) 2'6" x 10' side exhaust boxes
- 18 gram fiberglass filter media
- "Opti-Quiet" exhaust fans

Options/Upgrades

- ETL listed digital control panels
- ETL listed Mach-3 and Mach-3X heat systems
- ETL listed "Opti-Quiet" exhaust systems
- Full drive through configuration
- Pit kit upgrades (downdraft only)
- Above ground metal basement (downdraft only)
- Attached paint mixing and storage rooms
- Matching prep/refinishing stations
- VFD cabin pressure adjustment
- Remotely mounted control panel(s)
- "Opti-Cure" PLC/VFD control panel
- "Opti-Light" 360° lighting package upgrade, 6-tube fixtures
- Wall lighting kits
- Duct packages